

✓

L4 ANSWER 60 OF 321 CA COPYRIGHT 2004 ACS on STN  
 AN 136:41617 CA  
 ED Entered STN: 10 Jan 2002  
 TI Light-insulating mortar compositions containing cement,  
 fly ash, alumina, swelling agent and set  
 accelerator for improved setting rate, curing and reduced shrinkage  
 IN Na, Jong Yool; Kim, Sung Wan; Yoon, Sang Chun; Lee, Dae Woo; Kang, Il  
 Kyung; Shin, Il Seop  
 PA Hyundai Construction Co., Ltd., S. Korea; Korea National Housing  
 Corporation; Kumkang Korea Chemical Co., Ltd.  
 SO Repub. Korean Kongkae Taeho Kongbo, No pp. given  
 CODEN: KRXXA7  
 DT Patent  
 LA Korean  
 IC ICM C04B018-10  
 ICS C04B022-04  
 CC 58-3 (Cement, Concrete, and Related Building Materials)  
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	KR 2000014685	A	20000315	KR 1998-34228	19980824
PRAI	KR 1998-34228		19980824		

AB Light-insulating mortar compns. with improved setting rate, d., curing  
 properties and shrinkage resistance are prepd. The insulating mortar  
 compns. consist of 50-70 wt.% cement, 30-50 wt.% fly  
 ash, 1-10 wt.% swelling agent, 0.01-0.5 wt.% alumina,  
 0.1-0.8 wt.% set-accelerator (sodium carbonate), and 0.01-0.1 wt.%  
 cellulose ester. The swelling agent is a mixt. of calcium sulfoaluminate  
 and calcium sulfate or calcium oxide, a mixt. of alumina  
 cement and gypsum; a mixt. of calcium aluminate and  
 calcium sulfate and/or a mixt. of calcia and magnesia.  
 ST light insulating mortar compn setting rate curing shrinkage;  
 cement flyash swelling agent alumina set accelerator  
 mortar compn